



TOGNAZZONI S.R.L.

VIA R. LOMBARDI 18 - 46010 LEVATA DI CURTATONE (MANTUA)
TEL. 0376/290104 - FAX 0376/290205 - E-MAIL: info@tognazzoni.it

PRODUCT DATA SHEET

POLYETHYLENE LONG DISPOSABLE GLOVES

Article code	Description
122	SHORT POLYETHYLENE 5 FINGERED DISPOSABLE GLOVES LENGTH CM. ABOUT 33 - THICKNESS ABOUT 30 MY
	Packaging: 200 PIECES BOX
	Country of origin: ITALY
	Non-certified product
	Product composition: LOW DENSITY POLYETHYLENE
	Performed tests and checks: QUALITY CONTROL



TECHNICAL DATA SHEET

FILM USED FOR THE PRODUCTION OF POLYETHYLENE SHORT GLOVES
 LENGTH ABOUT CM. 33 - THICKNESS ABOUT 30 MY- Packaging: N. 200 PIECES (**Art. code 122**)

1)	CHEMICAL NATURE OF THE PRODUCT	Substance Polyethylene, chemical formula (C ₂ H ₄) _n Additives: Slip Agent (high) Antiblocking (high)
2)	PHYSICAL PROPERTIES <ul style="list-style-type: none"> • PHYSICAL STATUS..... • CHARACTERISTIC TEMPERATURES..... • SOLUBILITY • DENSITY 	At 20° C: plastic film Colour: translucent Melting point: 113° C. From the start of decomposition: approx. 300° C. In water at 20° C: not soluble From 0.92 to 0.95 g/cm ³
3)	TOXICOLOGICAL INFORMATION	These polymers can be considered as: - non-irritating to skin and eyes - not harmful if ingested Thermal decomposition products may be irritating to skin and mucous membranes.
4)	FIRST AID MEASURES	<ul style="list-style-type: none"> - In case of contact with hot products: treat as a thermal burn without chemical action (wash immediately and thoroughly with cold water). - Inhalation of thermal decomposition products: go to fresh air, consult a doctor.
5)	ENVIRONMENTAL PROTECTION	Do not dispose of into drains or into the natural environment. Comply with current prefectural regulations and decrees.
6)	SPECIAL INDICATIONS	This document applies to the product IN ACCORDANCE with the specifications provided by the TOGNAZZONI S.R.L. suppliers. The information contained in this technical data sheet is given in good faith and based on our latest knowledge of the product at the date of issue. The user's attention is drawn to the possible risks involved when a product is used for purposes other than those for which it is intended. This sheet must not be used or reproduced except for the purposes of prevention and safety.

DATA SHEET

FILM USED FOR THE PRODUCTION OF POLYETHYLENE SHORT GLOVES
 LENGTH ABOUT CM. 33 - THICKNESS ABOUT 30 MY- Packaging: N. 200 PIECES (**Art. code 122**)

	PROPERTIES	PE Film
	Melt Flow Index 190° C.....	2,0
	Density.....	0,924
THERMAL PROPERTIES	Melting point.....	113
	Embrittlement temperature.....	-75
	Softening temperature (Vicat 1 kg).....	96
MECHANICAL PROPERTIES	Yield strength.....	12
	Breaking load.....	12
	Elongation at break.....	22
	Secant modulus 1%.....	17
	Bending modulus.....	250
	Tear resistance (Eimendorf).....	580
	Izod Impact.....	200
	Impact resistance (Dart Drop Test).....	230
	Dynamic Coefficient of Friction (COF).....	70
	Hardness (Shore D).....	50
	Surfactants resistance (ESCR).....	100
OPTICAL PROPERTIES	Clarity.....	0,11
	Haza.....	46
	Gloss 45°.....	18
	Suggested thickness range.....	7,5
		65
		26 80
ADDITIVES	Slip Agent.....	High
	Antiblocking.....	High
	Others.....	
	<u>Key</u> features: good optical characteristics and drawdown	

The information and data contained herein are provided by us with the best of accuracy. However, this accuracy is not the subject of a guarantee and the data provided do not constitute or imply, in general terms, any guarantee or commitment by the Company. Any rights of patent holders are expressly reserved.